EV-1-63-IP

3 phase connection unit with built in open PEN detection

Do you need protection from open PEN on Three Phase PME infrastructures?

The **EV-1-63-IP** from matt:e is a simple single dedicated connection unit with built in **O-PEN** technology which allows for the connection of 1 x 63amp three phase load to the existing PME earthing facility.

The unit incorporates a 5 pole isolator with built-in shunt trip which disconnects all poles including CPC in the event of a fault, manually resettable in line with BS: 7671.

The matt:e *O-PEN* technology does not require earth rods or measuring electrodes to function correctly



Product Features


- Built in matt:e O-PEN technology
- IP 65 enclosure
- NO EARTH ELECTRODES REQUIRED
- Phase loss protection
- Built in 5 pole mains isolator with manually resettable shunt trip
- Standard 2 Year parts warranty
- Simple wire in wire out connection
- Option for 4 Pole B Type RCD for DC protection
- Designed and Built in the UK

...Simplifying EV connection





Dimensions and Specifications



40 - Ø25 - Ø32 - Ø40 Ø25 - Ø32 Ø40 - Ø50















Examp	ole I	Lav	out
-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		-∽,	

Description	Dedicated EV connection centre	
Input Volts	Nominal input voltage Three Phase 400V 50Hz	
Max Load	63 amps per Phase	
Cable Entry Facility	Top and bottom	
Terminal Capacity	16.0mm2	
Dimensions (H x W x D)	410mm x 310mm x 150mm	
Weight	Approximately 5kG	
Enclosure	ABS	
Ingress Protection	IP65	
Warranty	The matt:e <i>EV-1-63-IP</i> is guaranteed for a period of 2 years from the date of purchase. This warranty is limited to the replacement of faulty components only.	

...Simplifying EV connection



